

# CC Mosaics +

An antique flair with a modern twist, let our CC Mosaics + take center stage in your next project. Available in a soft color palette, this series is sure to brighten any room. With the versatility of porcelain mosaics, the CC Mosaics + Collection may be used in a variety of applications, so let those creative juices flow!




CC Mosaics + White Ice Bright 2"x4" Brick Beveled 12"x12" Mosaic



CC Mosaics + Mint Green Penny Round 12"x12" Mosaic

Glazed Porcelain Mosaics




12"x12"

# CC Mosaics +


Glazed Porcelain Mosaics



**Pearl Bright**  
12"x12" Penny Round  
UFCC125-12M



**Cream Bright**  
12"x12" Penny Round  
UFCC126-12M



**Sand Bright**  
12"x12" Penny Round  
UFCC123-12M




**White Ice Bright 2"x4"**  
12"x12" Brick Beveled  
U081BV-12M\*




**Taupe Bright 2"x4"**  
12"x12" Brick Beveled  
U789BV-12M\*



**White & Silver 1"x1" Matte**  
12"x12" Hexagon  
UFCCSLV-12M\*



**Mint Green Bright**  
12"x12" Penny Round  
UFCC127-12M




**Sky Blue Bright**  
12"x12" Penny Round  
UFCC124-12M



**Tender Gray Bright 2"x4"**  
12"x12" Brick Beveled  
U761BV-12M\*



**Black Bright 2"x4"**  
12"x12" Brick Beveled  
U759BV-12M\*



**White & Gold 1"x1" Matte**  
12"x12" Hexagon  
UFCCGLD-12M\*



**White Bright**  
12"x12" Herringbone  
UFCC128-12M\*



**Antique White Bright**  
12"x12" Herringbone  
UFCC129-12M\*



The product zoom above shows the antique finish effect that is a signature of the CC Mosaics + series  
\* Not available with antique finish



CC Mosaics + Antique White Bright 12"x12" Herringbone Mosaic



# Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM				
		Penny Round	Herringbone	Antique Herringbone	Brick	1x1 Hexagon
Water Absorption	C373	<=0.5%	<=0.5%	<=0.5%	<=0.5%	<=0.5%
Break Strength	C648	Min. 290	Min. 250	Min. 250	Min. 290	Min. 290
Scratch Hardness	MOH's Scale	3	3	3	2	3
Chemical Resistance	C650	Unaffected	Unaffected	Unaffected	Unaffected	Unaffected
Frost Resistance	C1026	Resistant	Resistant	Resistant	Resistant	Resistant
Group	See FAQ's	3	3	3	2	3
Deep Abrasion - Unglazed Tiles	C1243	-	-	-	-	-
PEI - Glazed Tiles	C1027	3	3	3	2	4
Minimum Bond Strength (PSI)	C482	165	165	165	165	165
Dynamic Coefficient of Friction (DCOF)	A137.1	<=0.21	<=0.22	<=0.22	<=0.21	<=0.30
Shade and Texture Rating	CTDA "V"	V2	V1	V1	V2	V2
Facial Dimensions	C499	Pass	Pass	Pass	Pass	Pass
Range of Thickness	C499	Pass	Pass	Pass	Pass	Pass
Warpage	C485	Pass	Pass	Pass	Pass	Pass
Wedging	C502	Pass	Pass	Pass	Pass	Pass

## Packaging Info

	Size	SF per carton	PC per carton
<b>Penny Round</b>	12"X12"	19.91	20
<b>Herringbone</b>	12"X12"	8.62	10
<b>Brick</b>	2"x4"	10.66	11
<b>1x1 Hexagon</b>	12"x12"	16.79	20