



## **Seattle**

Glazed & Polished Porcelain



**Blanco 35"x35" R** PO - I67170020 UP - I67170022



Blanco 24"x24" R PO - 167170030 UP - 167170026



**Blanco 24"x48" R** PO - I67170032 UP - I67170034



**Blanco 12"x24" R** PO - I67170028 UP - I67170024





## **Seattle**

Glazed & Polished Porcelain



Cinza 35"x35" R PO - 167180020 UP - 167180022



Cinza 24"x24" R PO - 167180030 UP - 167180026



**Cinza 24"x48" R** PO - 167180032 UP - 167180034



Cinza 12"x24" R PO - 167180028 UP - 167180024



## **Technical Specifications**

	p		
CHARACTERISTICS	STANDARD	DECLARED ASTM	
		POLISHED	UNPOLISHED
Water Absorption	C373	<=0.5%	<=0.5%
Break Strength	C648	Min. 335	Min. 335
Scratch Hardness	MOH's Scale	3	5
Chemical Resistance	C650	Unaffected	Unaffected
Frost Resistance	C1026	Resistant	Resistant
Group	See FAQ's	3	4
Deep Abrasion - Unglazed Tiles	C1243	Pass	Pass
PEI Glazed Tiles	C1027	3	4
Minimum Bond Strength (PSI)	C482	165	165
Dynamic Coefficient of Friction (DCOF)	A137.1	<=0.40	>=0.42
Shade and Texture Rating	CTDA "V"	V3	V3
Facial Dimensions	C499	Pass	Pass
Range of Thickness	C499	Pass	Pass
Warpage	C485	Pass	Pass
Wedging	C502	Pass	Pass

## **Packaging Info**

Size	SF per carton	PC per carton
12"X24"	18.94	10
24"X24"	19.05	5
24"x48"	15.28	2
35"X35"	17.22	2