

STONES

Pro Max

Neutral colors and low variation in design make the Pro Max series flow naturally in any space. This high performance stone look is meant to complement the Pro series by adding a bit of texture to its neutral hues.



Pro Max Sand 24"x24" R



Pro Max Sand 24"x24" R

Glazed Porcelain
24"x24" R

Pro Max

Glazed Porcelain

MARBLES

Floor Tiles



24"x24" R
60x60 cm



Ivory



24"x24" R UP
164270034A



Cement



24"x24" R UP
164270036A



Nude



24"x24" R UP
164270030A



Concrete



24"x24" R UP
164270038A



Sand



24"x24" R UP
164270032A

Technical Specifications

Characteristics	Standard	Declared ASTM
Water Absorption	C373	<=0.5%
Break Strength	C648	Min. 350
Scratch Hardness	MOH's Scale	4
Chemical Resistance	C650	Unaffected
Frost Resistance	C1026	Resistant
Group	C1027	3
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction (DCOF)	A137.1	>=0.42
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	C499	Pass
Range of Thickness	C499	Pass
Warpage	C485	Pass
Wedging	C502	Pass

Packaging Info

Size	SF. Per Carton	Pieces Per Carton
24"x24"	23.25	6