

lungarno
CERAMICS



ZELLIGE BESPOKE

ZELLIGE BESPOKE

Authentic Zellige Tile



COLOR AVAILABILITY - 2" x 6" Long Oval



Desert Pearl
ZBDESPEA26OVL



Nomad Sand
ZBNOMSAN26OVL



Twilight Bloom
ZBTWIBLO26OVL



Sundried Clay
ZBSUNCLA26OVL



Indigo Mist
ZBINDMIS26OVL



Espresso Noire
ZBESPNOI26OVL

COLOR AVAILABILITY - 4" x 4"



Desert Pearl
ZBDESPEA44L




Nomad Sand
ZBNOMSAN44L



Twilight Bloom
ZBTWIBLO44L



Sundried Clay
ZBSUNCLA44L



Indigo Mist
ZBINDMIS44L



Espresso Noire
ZBESPNOI44L

SIZE AVAILABILITY

	NOMINAL SIZE	ACTUAL SIZE	THICKNESS	PC/CARTON	SQ.FT/CARTON
	2" x 6"	N/A	1.5 cm	100	9.69
	4" x 4"	N/A	3/8"	100	10.76

ZELLIGE BESPOKE

Authentic Zellige Tile



COLOR AVAILABILITY - Crosshatch



Desert Pearl
ZBDESPEACH



Nomad Sand
ZBNOMSANCH



Twilight Bloom
ZBTWIBLOCH



Sundried Clay
ZBSUNCLACH



Indigo Mist
ZBINDMISCH



Espresso Noire
ZBESPNOICH

COLOR AVAILABILITY - Circles



Desert Pearl
ZBDESPEACIRC



Nomad Sand
ZBNOMSANCIRC



Twilight Bloom
ZBTWIBLOCIRC



Sundried Clay
ZBSUNCLACIRC



Indigo Mist
ZBINDMISCIRC



Espresso Noire
ZBESPNOICIRC

SIZE AVAILABILITY

		NOMINAL SIZE	ACTUAL SIZE	THICKNESS	PC/CARTON	SQ.FT/CARTON
	Cross-Hatch	11.80" x 11.80"	N/A	7/16"	11	10.76
	Circles	12.80" x 12.20"	N/A	7/16"	10	10.76

ZELLIGE BESPOKE

Authentic Zellige Tile



TECHNICAL SPECIFICATIONS	2" x 6"	4" x 4"	Mosaics
 Material Type	Zellige Terracotta	Zellige Terracotta	Zellige Terracotta
 Finish	Glossy	Glossy	Glossy
 Edge	Hand-Cut	Hand-Cut	Hand-Cut
 Color Variation	V3	V3	V3
 Printing	N/A	N/A	N/A
 Installation	Wall	Wall	Wall
 Usage	Residential / Commercial	Residential / Commercial	Residential / Commercial
 Grout Joint Recomm.	N/A	N/A	N/A
 Thickness	.59"	3/8"	3/8"
 Shower Pan	No	No	No
 Pool Lining*	No	No	No
 Fireplace Surround*	Yes	Yes	Yes
 Frost Resistant	No	No	No

*Proper installation methods must be followed per project. Please reference TCNA for more information.

Special Considerations for Zellige Tile:

- Variation in caliber, flatness, straightness, texture, design and shade are present and inherent to the manufacture process of real zellige products.
- Chips, pinholes and other imperfections are common in zellige tiles and are not defective. Material with these characteristics are not subject for exchange or return.
- It is highly recommended to mix pieces from multiple cartons prior to installation in order to achieve a natural shade variation throughout the installation.
- Zellige tiles look beautiful installed with or without grout, and with a variety of grout joint thicknesses. When installing in a wet area, grouting and sealing will be necessary.
- Industry standard recommends overage by 15% in order to account for shortage due to tile cuts, breakage and future repairs.