

lungarno
CERAMICS



MARRAKESH

MARRAKESH offers the beauty and historic details of true Zellige tiles while still making it a perfect fit for design today. This collection is offered in two classic wall formats, and paired perfectly with decorative floor tiles.

THE DETAILS:

- 4" x 4" or 2.5" x 8" wall tiles in soft and neutral, yet rich tones with a semi-gloss finish
- 8" x 8" floor tiles in unique patterns with slight glossy ink effect, paired effortlessly with any of the wall tiles

STYLE IT:

- Kitchen backsplashes with natural wood cabinetry and brass fixtures
- Floor-to-ceiling shower walls for a spa-inspired feel
- Bold and playful laundry or bathroom floors



Photo features Meknes Marine 2.5" x 8"



Photo features Bahia 8" x 8"



Photo features Medina Green 4" x 4"

MARRAKESH

Ceramic Wall and Porcelain Floor Tile



COLOR AVAILABILITY - WALL



Sahara White
MARSAH44




Tantan Beige
MARTAN44




Sidi Salt
MARSID44



Medina Green
MARMED44



Meknes Marine
MARMKN44




Berber Black
MARBER44



Sahara White
MARSAH258




Tantan Beige
MARTAN258




Sidi Salt
MARSID258



Medina Green
MARMED258



Meknes Marine
MARMKN258



Berber Black
MARBER258

COLOR AVAILABILITY - FLOOR



Macaal
MARMAC88



Bahia
MARBAH88






Melah
MARMEL88



Rubeli
MARRUB88

SIZE AVAILABILITY

	NOMINAL SIZE	ACTUAL SIZE	THICKNESS	PC/CARTON	SQ.FT/CARTON
	4" x 4"	3.94" x 3.94"	3/8	44	4.73
	2.5" x 8"	2.44" x 7.95"	3/8	38	5.17
	1" x 8" Trim (Wall)	0.98" x 7.95"	3/8	88	N/A
	8" x 8"	7.87" x 7.87"	3/8	13	5.60

MARRAKESH

Ceramic Wall and Porcelain Floor Tile



TECHNICAL SPECIFICATIONS	WALL	FLOOR
Material Type	Ceramic (Double-Fired)	Glazed Porcelain
Finish	Semi-Gloss	Matte
Edge	Pressed	Pressed
Color Variation	V3	V3
Printing	N/A	Inkjet
Installation	Wall	Wall / Floor
Usage	Residential / Commercial	Residential / Commercial
Grout Joint Recomm.	1/16" or No Grout Joint	1/8"
Thickness	3/8"	3/8"
Shower Pan	No	Yes
Pool Lining*	No	Yes
Fireplace Surround*	Yes	Yes
Frost Resistant	No	Yes

*Proper installation methods must be followed per project. Please reference TCNA for more information.

TEST RESULTS	WALL	FLOOR
Water Absorption (C373)	> 10%	≤ 0.5 %
Breaking Strength (C648)	N/A	≥ 250 LBS
Surface Abrasion (MOHS)	N/A	5.0
Chem. Resistance (C650)	N/A	Resistant
D.C.O.F. (A137.1)	N/A	> 0.42
Scratch Hardness (P.E.I)	N/A	4

Special Considerations for Wall:

- Variations in caliber, flatness, straightness, texture, design and shade are present in the artisanal manufacture process of this product.
- Special and vibrant glazes can produce an intentional crackle upon production, in transport or after installation.
- Dry-stacking is recommended for wall tile, although not required. When installing in a wet area, a waterproof member is required prior to installation, and grouting and sealing will be necessary.



Photo features Melah 8" x 8"