





BEIGE

 SLIGHT VARIATION




1095603 - 17.36"x34.84" Rectified 



1094703 - 18"x18"
Nominal Pressed



1094783 - 12"x24" Nominal Pressed 



1094699 - 12"x12" Nominal Pressed



1094711
6"x6" Nominal Cut



1094715
2"x2" Mosaic (12"x12")



1094719
2"x2" Hexagon Mosaic (12"x12")



1094707
3"x12" Bullnose

GLAZED PORCELAIN

17.36"x34.84" Rectified, 18"x18" Nominal - 12"x24" Nominal - 12"x12" Nominal - 6"x6" Nominal mosaics - bullnose



GREY

V2 SLIGHT VARIATION



1095605 - 17.36"x34.84" Rectified



1094705 - 18"x18" Nominal Pressed



1094785 - 12"x24" Nominal Pressed



1094701 - 12"x12" Nominal Pressed



1094713
6"x6" Nominal Cut



1094717
2"x2" Mosaic (12"x12")



1094721
2"x2" Hexagon Mosaic (12"x12")



1094709
3"x12" Bullnose



NOCE

V2 SLIGHT VARIATION



1095604 - 17.36"x34.84" Rectified ^{Ω†}



1094704 - 18"x18" Nominal Pressed



1094784 - 12"x24" Nominal Pressed ◆



1094700 - 12"x12" Nominal Pressed



1094712 6"x6" Nominal Cut



1094716 2"x2" Mosaic (12"x12")



1094720 2"x2" Hexagon Mosaic (12"x12")



1094708 3"x12" Bullnose

COLOR SPECIFICATIONS AND SIZES AVAILABLE

Nominal Size	BEIGE	NOCE	GREY
17.36"x34.84" Rectified Ω †	1095603	1095604	1095605
18"x18" Nominal Pressed	1094703	1094704	1094705
12"x24" Nominal Pressed \blacklozenge	1094783	1094784	1094785
12"x12" Nominal Pressed	1094699	1094700	1094701
6"x6" Nominal Cut	1094711	1094712	1094713
2"x2" Mosaic (12"x12")	1094715	1094716	1094717
2"x2" Hexagon Mosaic (12"x12")	1094719	1094720	1094721
3"x12" Bullnose	1094707	1094708	1094709

PACKAGING

NOMINAL SIZE	METRIC (CM)	THICKNESS (MM)	PIECES PER BOX	SQ. FT PER BOX	WEIGHT PER BOX	BOXES PER PALLET	WEIGHT PER PALLET
17.36"x34.84" Rectified Ω †	44.5x88.49	10 mm	3	12.6	55.4	27	1500
18"x18" Nominal Pressed	45x45	9 mm	7	15.75	64.5	32	2066
12"x24" Nominal Pressed \blacklozenge	30x60	9 mm	7	14	57.4	48	2755
12"x12" Nominal Pressed	30x30	9 mm	14	14	57.4	48	2755
6"x6" Nominal Cut	15x15	9 mm	34	8.5	35	72	2520
2"x2" Mosaic (12"x12")	30x30	9 mm	10	10	41	45	1900
2"x2" Hex Mosaic (12"x12")	30x30	9 mm	10	10	41	45	1900
3"x12" Bullnose	7.5x30	9 mm	12	3	12.0	168	2071

ALL OTHER SIZES WILL BE PACKAGED AS ORDERED.
PLEASE CONTACT FLORIM CUSTOMER SERVICE AT 877-FLORIM1 FOR PACKAGING INFORMATION.

\blacklozenge MINIMUM GROUT SIZE RECOMMENDED = 5 MM (OR APPROX. 3/16" IF STAGGERED TILE PLACEMENT, WE RECOMMEND USING A 30% OFFSET. IF SPECIFIED BRICK PATTERN WITH 1/2 PATTERN MANDATORY, A BIGGER GROUT IS RECOMMENDED TO HIDE IMPERFECTIONS OF INSTALLATION (MINIMUM 1/4").

† RECTIFIED MATERIAL IS NOT MODULAR WITH NOMINAL PRESSED MATERIAL.

Ω FOR STAGGERED APPLICATIONS, WE RECOMMEND 30% OFFSET.

SHADE VARIATION



V1

UNIFORM APPEARANCE
Differences among pieces from the same production run are minimal.



V2

SLIGHT VARIATION
Clearly distinguishable differences in texture and/or pattern with similar colors.



V3

MODERATE VARIATION
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly.



V4

SUBSTANTIAL VARIATION
Random color differences from tile to tile, so that one tile may have totally different colors from that on other tiles. Thus, the final installation will be unique.

TECHNICAL SPECIFICATIONS

	PEI	IV	ASTM C1027
Surface Abrasion			ASTM C1027
Water Absorption		≤ 0.5%	ASTM C373
Chemical Resistance		CLASS A	ASTM 650
Coefficient of Friction	(Dry)	≥ 0.80 •	ASTM C1028
	(Wet)	≥ 0.60 •	ASTM C1028
	(Dynamic)	≥ 0.42 •	ANSI 137.1
Stain Resistance		CLASS A	ASTM C1378
Breaking Strength		≥ 400 (9mm)	ASTM C648
Resistance to freeze		RESISTANT	ASTM C1026
Scratch Hardness		≥ 7	MOHS

ALL FLORIM USA PRODUCTS MEET OR EXCEED ALL STANDARDS IN ANSI A137.1.

• DUE TO THE INHERENT NATURE OF FIRED PORCELAIN TILE, IT IS IMPORTANT TO NOTE THAT THE COEFFICIENT OF FRICTION MAY VARY WITHIN AND BETWEEN PRODUCT RUNS.

WHY PORCELAIN?

There are many reasons to choose impervious porcelain tile over other floor coverings. It offers the largest array of design options and holds its value the longest. In a comparison between the many different flooring options, porcelain tile offers one of the most durable and least expensive options over the lifespan of the building.

Benefits of Porcelain Tile

- Impervious to water
- Easy to maintain
- Variety of design options
- Environmentally friendly
- Resistant to germs and bacteria
- Fade resistant
- Fire resistant
- Durable - best long-term value vs. other floor coverings

HOW TO MAINTAIN YOUR PORCELAIN TILE

- Sweep or vacuum regularly.
- Wash with a household cleaner and hot water then rinse with clean water (do not use wax, oil-based, or abrasive cleaners).

Scan this barcode for more care, maintenance, and installation tips at www.florimusa.com



Colors Shown in this brochure may vary from actual product.
Final selection should be made from actual product samples.



40% RECYCLED CONTENT



LEED

Environment
PRIORITY ONE



PROGRESS THAT TOUCHES AND INVESTS IN THE ENTIRE SOCIETY

As a active member of the U.S Green Building Council, Florim spreads awareness to the entire American communities and encourages towards the use of building solutions inspired by environmentally friendly practices. Using Florim products for project implementation, will positively contribute in obtaining scores and points required for earning the LEED certification (Leadership in Energy and Environmental Design).

A COMMITMENT TO THE DEVELOPMENT OF PRODUCTS FOR A CONSCIOUS BUILDING TRADE

Florim offers products containing recycled material. The adoption of eco-compatible production systems is merit of Italian designs produced in the U.S.

TECHNICAL DEVELOPMENT THAT CONSIDERS THE NATURAL ENVIRONMENT

Florim commits to the eco-compatible project and translates the same into an avant-gard production process, minimizing the negative impact on the environment.



LEED

Environment
PRIORITY ONE

PROGRESS THAT TOUCHES AND INVESTS IN THE ENTIRE SOCIETY

As a active member of the U.S Green Building Council, Florim spreads awareness to the entire American communities and encourages towards the use of building solutions inspired by environmentally friendly practices. Using Florim products for project implementation, will positively contribute in obtaining scores and points required for earning the LEED certification (Leadership in Energy and Environmental Design).

A COMMITMENT TO THE DEVELOPMENT OF PRODUCTS FOR A CONSCIOUS BUILDING TRADE

Florim offers products containing recycled material. The adoption of eco-compatible production systems is merit of Italian designs produced in the U.S.

TECHNICAL DEVELOPMENT THAT CONSIDERS THE NATURAL ENVIRONMENT

Florim commits to the eco-compatible project and translates the same into an avant-guard production process, minimizing the negative impact on the environment.



300 International Blvd. Clarksville, TN 37040
toll free 877 - Florim1 (356-7461)
tel. 931 645 5100
www.florimusa.com

**FLORIM
USA**